

# 11.4.1. [ ](11.4.1. Registratic Template)

## 11.4.1. [ ]

- Error name:  
[ ]“example”[ ] [%x20-21 /%x23-5B /%x5D-7E][ ]
- Error usage location:  
[4.1.2.14.2.2.15.27.2][ ]
- Related protocol extension:
- ~~Change controller~~ [ ]  
[ ]RFC[ ]“IETF”[ ]URI[ ]
- Specification document(s):  
[ ]URI[ ]

### 11.4.1. Registration Template

Error name:  
The name requested (e.g., "example"). Values for the error name MUST NOT include characters outside the set %x20-21 / %x23-5B / %x5D-7E.  
Error usage location:  
The location(s) where the error can be used. The possible locations are authorization code grant error response (Section 4.1.2.1), implicit grant error response (Section 4.2.2.1), token error response (Section 5.2), or resource access error response (Section 7.2).  
Related protocol extension: The name of the extension grant type, access token type, or extension parameter that the error code is used in conjunction with.

Change controller: For Standards Track RFCs, state "IETF". For others, give the name of the responsible party. Other details (e.g., postal address, email address, home page URI) may also be included.

Specification document(s): Reference to the document(s) that specify the error code, preferably including a URI that can be used to retrieve a copy of the document(s). An indication of the relevant sections may also be included but is not required.

---

Revision #1

Created Wed, Mar 25, 2020 11:40 PM by ☐☐

Updated Wed, Mar 25, 2020 11:40 PM by ☐☐